



ARMSTRONG BIOGUARD PLAIN 15 mm



- Armstrong BIOGUARD PLAIN combines excellent cleanability and resistance to disinfectants. Along with its antimicrobial performance, it is an ideal solution for healthcare environments
- Good sound attenuation (35 dB)
- Excellent light reflectance (87%)
- ISO 5
- Ideal for healthcare environments with average or severe risk of infection





ARMSTRONG BIOGUARD PLAIN 15mm KNAUFGEILING Solutions



Edge details	Board Discourse L24	Tegular 24			Tegulo	15		
Thickness (mm)	15	15			15	- -		
Dimensions (mm)	600 x 600	600 x 600			600 x 600			
	1200 x 600	1200 x 600			1200 x 600			
System	Exposed demountable - System C Exposed - Bandraster, demountable - System I.3 Exposed - Corridor, demountable - System F.3							
Weight	3.5 - 3.6 kg / m ²							
Colour	White							
Sound absorption	EN ISO 354 $\alpha_{w} = $ 0.20(L) as per EN ISO 1165	54 - Class F						
	Frequency f (Hz)	- Cluss E	125	250	500	1000	2000	4000
	$\alpha_{_{\mathrm{P}}}$		0.40	0.25	0.15	0.15	0.20	0.30
	NRC = 0.20 as per ASTM C 423							
Sound attenuation	EN ISO 10848-2 D _{n,f,w} = 35 dB as per EN ISO 717-1							
Sound reduction	EN ISO 10140-2 R _w = 19 dB as per EN ISO 717-1							
Fire reaction	Euroclass A2-s1, d0 as per EN 13501-1 RUS KM1 (G1, V1, D1, T1) as per FZ 123						123	
Light reflectance	87%							
Thermal conductivity	λ = 0.060 W/m K as per EN 12667							
Humidity resistance	95% RH							
Clean room	ISO 5 as per EN ISO 14644-1							
Indoor air quality	A+ E1							
Cleanability			+					
Sustainability	81 - 42%							

Products may vary from country to country. Please contact your local sales representative. For further information and legal notice, please visit our website.

